

65W external power adapter

The Shuttle Accessory PE65 is an external AC to DC power adapter meant as a replacement device for certain Shuttle products. It provides a maximum output wattage of 65W.

XPC Accessory PE65



Images for illustration purposes only.

Feature Highlight	
Package contents	<ul style="list-style-type: none"> Power adapter (Model APD DA-65A19) with DC cable and DC output plug AC power cord with Euro plug Quick guide
Input	<ul style="list-style-type: none"> Input Voltage: 100~240 VAC, 50~60 Hz Input Current: max. 1.6 A
Output	<ul style="list-style-type: none"> Output Voltage: 19 V DC Output Current: max. 3.42 A Output Wattage: max. 65 W
Cooling	<ul style="list-style-type: none"> Passive, fanless cooling
Connectors	<ul style="list-style-type: none"> DC connector: 5.5/2.5mm (outer/inner diameter) AC connector: Euro plug (2-pin)
Environmental	<ul style="list-style-type: none"> Operation temperature range: 5~40 °C Relative humidity range: 10~90% (non-condensing)
Safety/EMI	<ul style="list-style-type: none"> Compliance and Logos: CE, WEEE and others
Dimensions	<ul style="list-style-type: none"> Dimensions: 110.5 x 48.5 x 31.5 mm (LWH) Weight: ca. 210 g
Compatibility	<p>Compatible to these Shuttle XPC products:</p> <ul style="list-style-type: none"> 1L Slim PC: XS35/XS36-Series, DS47, DS407T, DS437(T), DS57U(x), DS67U(x), DS68U(x), DS77U(x), DS10U(x), DS20U(x)(V2), DL10J, DL20N(6)V2 3L Slim PC: XC60J Nano PC: NC01U(x), NC02U(x), NC03U(x), NC10U(x), NC40U(x), NS02A/E(V2) AIO PC: P20U, P22U, P25N, P51U(3), P52U(3), P90U(x), P92U(x), X50V2(x)-X50V8(x) OMNINAS: KD20, KD21, KD22, KS10

© 2024 by Shuttle Computer Handels GmbH (Germany). All information subject to change without notice. Pictures for illustration purposes only.

