© 2022 by Shuttle Computer Handels GmbH (Germany). All information subject to change without notice . Pictures for illustration purposes only

90W external power adapter

The Shuttle Accessory PE90 is an external AC to DC power adapter meant as a replacement device for certain Shuttle products. It provides a maximum output wattage of 90W.

Feature Highlight Power adapter (90W) with DC cable and DC Package output plug AC power cord with Schuko-plug contents Quick guide Input Voltage: 100~240 VAC, 50~60 Hz Input Input Current: max. 1.5 A Output Voltage: 19 V DC Output Current: max. 4.74A Output Output Wattage: max. 90W Cooling Passive, fanless cooling DC connector: 5.5/2.5mm (outer/inner diameter) Connectors AC connenctor: angled Schuko safety plug (with earthing contact) Operation temperature range: Environ-5~35 °C (41~95 °F) mental Relative humidity range: 10~90% (non-condensing) Safety/EMI Compliance and Logos: CE, WEEE and others Dimensions: 127 x 51 x 30.5 mm (LWH) **Dimensions** Weight: 310 g (max.) Compatible to the 90W power adapter of the following Shuttle products: Slim PC: DS61, DS81, DS87, DH110(SE), DH170, DQ170, DH270, DH310(V2), DH310S, DH370, DH410(S), DH470, XH61(V), XH81(V), XH97V, XH110(V), XH170, XH310(R)(V) Compatible to the Shuttle Edge Series: EN01J3, EN01J4, EN01E, EN01B Backward compatible to the 65W power adapter of the following Shuttle products: Slim-PC: DS47, DS407T, DS437(T), DS57U(x), DS67U(x), DS68U(x), DS77U(x), DS10U(x), DS20U(x) Compatibility XC60J Nano-PC: NC01U(x), NC02U(x), NC03U(x), NC10U(x) All-in-One PC: X50, X50V4, X50V5(U3), X50V6(U3), X50V7(U3), X50V8(U3), P20U, P22U, P51U(3), P52U(3) P90Ux, P92Ux OMNINAS: KD20, KD21, KD22 Backward compatible to the 40W power adapter of the following Shuttle products: Slim-PC: XS35/XS36 series, DX30, DL10J, DL20N(6) All-in-One PC: X50V2 (Plus), X50V3(L) **OMNINAS: KS10**

XPC Accessory PE90



Images for illustration purposes only.



DH410



XH310RV



DX30, DL10J, DL20N

